OWNER MANUAL

PLEASE SAVE THIS MANUAL
FOR FUTURE REFERENCE

La Fleur™

FOOT-SPA



GULFSTREAM

Cleanjet™, La Fleur™,Gulfstream Plastics™ are trademarks of Gulfstream Plastics Ltd.

© 2009 All rights reserved. Design and Specifications are subject to change without notice

Table of Contents

Owner Manual

Safety and Precautions 1-2

Identifying Parts 3-4

Foot-spa Clearance 5

INSTALLATIONS

Attaching Seat 6

Jet Assembly 7-9

Plumbing Connections 10

Operations and Use 11-13

Cleaning & Maintenance 14

Warranty & Service 15

SAFETY & PRECAUTION

Thank you for purchasing the La Fleur spa from Gulfstream Plastics Ltd. Please carefully read instructions before installing the spa. Carefully follow the instructions, your spa will give you years of beauty and service.

This product is to be connected to a branch circuit outlet protected by a Class A GROUND FAULT CIRCUIT INTERRUPTER (GFCI), and the GFCI shall be tested regularly for continued protection and correct operation. If a Class A GFCI protected outlet is not available, DO NOT USE THIS PRODUCT! Please contact a licensed electrician for installation of a Class A GFCI according to local electric codes, or equivalent.

Warning THIS PRODUCT IS FOR IN DOOR USE ONLY
DISCONNECT POWER SUPPLY CORD BEFORE SERVICING AND CLEANING

Foot-spa must be installed by a licensed plumber and electrician in accordance with local codes. Plumbing and Electrical Installation instructions must be adhered to in order for the warranty to be in effect and to insure the utmost in safety. Chair and spa have a maximum seating capacity of **350 pounds**.

Warning If a crack occurs in the glass bowl, **DO NOT** manually handle the bowl unless the proper attire is worn. Under no circumstances must the bowl be used by your customers as you can be held accountable for any injury that may occur. Gulfstream Plastics is not liable for any injury that may occur.

BASIC PRECAUTIONS SHOULD ALWAYS BE OBSERVED, INCLUDING THE FOLLOWING:

1. Read and follow all instructions
2. **DANGER**. To reduce the risk of injury, do not permit children to use this unit unless they are supervised at all times
3. Use this unit only for its intended use as described in this manual. Do not use attachments that are not Recommended by the manufacturer.
4. Never drop or insert any object into any opening.
5. Do not block jets during whirlpool operation.
6. The unit must be connected to an electrical supply circuit that is protected by a ground fault circuit interrupter.
7. The clean jet motor is magnetically driven and is insulated twice. Therefore it does not require to be bonded. Save these instructions

Warning

1. Excessive water temperature is dangerous and should be checked BEFORE use.
2. Maximum temperature of the water should never exceed 100 degrees F.
3. Always enter and exit the Foot Spa slowly and carefully.
4. NEVER bring and / or operate any electrical devices into or near the Foot Spa.

SAFETY & PRECAUTION

GROUNDING METHODS

Because this unit must be connected to a circuit with a ground-fault circuit interrupter (GFCI), DO NOT use a grounding adapter.
The use of a grounding adapter is prohibited in Canada by Part I of the Canadian Electrical Code.

GROUNDING INSTRUCTIONS

This appliance must be plugged into an outlet equipped with a ground-fault circuit interrupter. The ground-fault interrupter can be in the out-let shown in illustration A or in the circuit breaker (fuse) box. If your outlet or circuit breaker (fuse) box is not equipped with a ground-fault interrupter, you must have your electrician install one.

In the event of an electrical short-circuit, the ground-fault circuit interrupter will turn off the electrical power to the unit immediately, greatly reducing the likelihood of serious injury. This appliance is for use with a nominal 120-volt circuit and has a grounding plug that looks like the plug illustrated in sketch B. The outlet must be properly installed and grounded in compliance with all local codes and ordinances.

If it is necessary to use an extension cord, use only a three-wire extension cord that has a three-blade grounding plug and a three-blade grounding plug and a three-slot receptacle that will accept the plug on the appliance. Replace or repair a damaged cord.



COMPLIANCE WITH LOCAL CODES OR INSPECTIONS IS THE RESPONSIBILITY OF THE PURCHASER AND/OR INSTALLER

OPERATION AND USE INSTRUCTIONS

READ AND FOLLOW ALL INSTRUCTIONS.

1. IMPORTANT! At the end of the day, ALWAYS turn the main power OFF!
2. DANGER: To reduce the risk of injury, do not permit children to use this unit unless they are closely supervised at all times.
3. CAUTION: This unit should not be used by persons with open wounds, cuts or sores on their feet or legs, or by persons with poor circulation, or by persons with heart conditions. If in doubt, the client should consult with his or her physician.
4. Use this unit only for its intended use as described in this manual. Do not use attachments not recommended by the manufacturer
5. Do no operate with a damaged cord or plug. If the Mirage Pedicare System malfunctions or is damaged in any manner, contact an authorized service representative for examination or repair.
6. Never drop or insert any objects into any opening.
7. Do not operate this unit without the guard (screen) over the suction fitting located in the bottom of the enameled bowl.
8. Do not block jets during pedicure operation.
9. Water temperature should be checked before use. Water temperature should never exceed 104 degrees Fahrenheit.
10. Never bring any electrical devices into the pedicure or operate electrical devices near it.
11. The unit must be connected to a supply circuit that is protected by a ground-fault circuit interrupter (GFCI).
12. Connect the Mirage pedicure only to a properly grounded outlet. See grounding instructions.
13. Close supervision is necessary when the Mirage Pedicare System is used by, on or near children or invalids.

IDENTIFY YOUR FOOT-SPA



1. Glass Bowl
2. Water Filler
3. Back Cushion & Massage
4. Headrest Pillow
5. Wooden Armrest
6. Flip-out Manicure Tray
7. Seat Cushion
8. Adjustable Footrest
9. Front Control Panel
10. Jet
11. Drain
12. Water Control
13. Jet Control
14. Hand Spray
15. Drain Control

Control Panel



IDENTIFY YOUR FOOT-SPA

SEAT OPERATION

Armrest can be raised up/down



SPA DIMENSION



FOOT-SPA CLEARANCE



TYPICAL FOOT-SPAS



Attaching The Seat to The Base


Attach trays or remote stand to armrest with screws provided
Align the seat with the pre-drilled holes on the base then tightly secure with the nuts and bolts provided.

Cleanjet Installation



Align fingers to the opening, turn counter-clockwise and pull in the arrow direction to remove jet cover



Align jet cover on the jet housing then turn clockwise to install jet cover

Cleanjet Max Components



Cleanjet Max Installation



Snap the jet cover and impeller onto the anchors located on the plate in the direction of arrow as shown. Make sure the jet snapped securely on the plate.

To remove, simply pull the jet cover and impeller from the anchors

Cleanjet Max SL Installation



Place the poly liner and drain plug firmly onto the tub, hold the handle and push into the opening located under the footrest in the direction of the arrow until it is secured. Make certain that the jet is snapped firmly on the tub wall and the handle is secured to the opening.

To remove, simply pull out the handle with jet cover and impeller from the opening

Pull out the lock as shown to remove cover and impeller from the handle

Cleanjet Max Assembly

Warning Some jet components are located under the base unit behind the tub wall

Disconnect the foot-spa unit from any electrical source before disassemble the jet unit. All surface must be dry. Some jet components may contain sharp object and very hot after usage.

To remove the jet unit follow the steps below

1. Carefully detach the Jet Cover and Impeller from Tub Wall
2. Turn the Cap Head counter-clockwise to remove, carefully pull the metal claim and the jet motor backward There may be water sealant between the Motor and Tub wall

To assemble the jet unit, install in the reverse steps above. You may have to apply some water sealant between the Motor and The Tub wall





Plumbing Connections

Gravity Drain



Power Drain



1. Discharge pump may be connected to an existing sink drain or floor drain. It can also pump up to 7 ft high, but this will increase the length of the drain time. The drain connection is at the rear of the unit by a 3/4" fitting.

2. Gravity drain uses a standard gravity drain. A floor drain is recommended. Connection via a P-Trap is supplied.

3. Hot and cold water supply connections are located at the rear of the unit (½" fittings).
   Please be advised that the hot and cold water supply lines are not fitted with optional back flow Preventers unless ordered at initial sale.

4. Have a qualified licensed electrician to install the wiring according to local codes.
   The Cleanjets are 1/10 hp, 120V, 1.2 AMP 60OHZ. A 15 amp GFI protected circuit must be used to supply power to the unit. The roller back massage chair uses a 115V supply.

5. Spa base should be anchored securely to the floor. The base may be anchored through the opening in the back of the base wherever access is convenient for the installer.

FAILURE TO ANCHOR THE BASE MAY RESULT IN PERSONAL INJURY OR DAMAGE TO THE UNIT. DAMAGE AS A RESULT WILL VOID THE WARRANTY.

OPERATIONS & USE

Control Panel



1. **To fill water:**
   The foot-spa is provided with a single hot and cold mixing valve located on the front of your spa(far left). This is a pressure balance valve that requires you to lift the handle to start the water flow and to adjust to the temperature that is desired. The clean jet motor must be completely submerged in water.

   CAUTION: DO NOT USE FOAMING, SUDSING OR MINERAL OIL BASED ADDITIVES IN THE WATER.

2. **To start whirlpool:**
   Press the button that is situated next to the water fill lever. This will start your Clean Jet motor. You may stop the whirlpool function at any time by pressing the button again.

3. The foot-spa is equipped with a hand held sprayer. To activate the hand shower, pull the hand shower from the receptacle and depress the thumb control on the sprayer handle. This will turn on the water. When you release pressure on the thumb control this will turn the water off.

4. **To drain whirlpool tub:**
   The spa is equipped with a built in optional discharge pump. Open the drain plug by turning the control knob with which is situated at the far right of the spa base. Press discharge pump timer button situated far left on front of base (pump will run for approx. 2 min.) Average time for drain 1 minute.

5. 9600 & 9700 chairs Shiatsu Roller back massage is equipped with a state of-the-art massage system. The massage system is easy to use; the remote has a one touch power that starts select your own massage. You can also adjust the front to rear position of the chair and the reclining back. By using the remote your client can adjust the back to the most comfortable position.

BASIC PRECAUTIONS SHOULD ALWAYS BE OBSERVED, INCLUDING THE FOLLOWING:

1. Read and follow all instructions
2. **DANGER**. To reduce the risk of injury, do not permit children to use this unit unless they are supervised at all times
3. Use this unit only for its intended use as described in this manual. Do not use attachments that are not Recommended by the manufacturer.
4. Never drop or insert any object into any opening.
5. Do not block jets during whirlpool operation.
6. The unit must be connected to an electrical supply circuit that is protected by a ground fault circuit interrupter.
7. The clean jet motor is magnetically driven and is insulated twice. Therefore it does not require to be bonded. Save these instructions

9700 Shiatsu Remote Control

Please refer to instruction manual for operations

9500/9600 Shiatsu Remote Control

Please refer to instruction manual for operations

CLEANING & MAINTENANCE

Please refer the diagrams to remove jet covers for cleaning

Gulfstream Plastics Ltd. highly recommends the following cleaning regimen. You should always contact your local governing agency for their specific cleaning and disinfecting requirements and regulations for pedicure spas. For your clients safety, always use the regulations as a minimum standard for cleaning and disinfecting. Combining your states standards with the regimen listed below will provide your clients with a safe and healthy pedicure spa environment experience.

Routine maintenance:

Powdered cleansers or abrasives are **NOT RECOMMENDED**. A clean towel or sponge, are all that are usually needed. A soft bristled brush may be used when excessive residue is present. Use a mild soap and water solution to clean the upholstery, but do not over wet. Wipe dry with a clean towel. No internal maintenance of the spa components is necessary. Remove clean jet caps and spray with disinfectant after each use. For extra protection, our recommendation is that the system be flushed daily or weekly depending on use. To flush the clean jet system fill spa with hot water to just above the jets. Add disinfectant. Run whirlpool for 15 minutes, drain and then wipe dry with clean soft cloth.

NOTE:

Cleaning or sanitizing is NOT disinfecting. According to the Centers for Disease Control and Prevention (CDC), and the US Environmental Protection Agency (EPA), disinfecting occurs only when there is a reduction of pathogenic microbes at 99.999%. Sanitizing is only a reduction of 99.9%. Cleaning of whirlpool pedicure spas requires surfactant and chelating detergents that are low-foaming and have the ability to remove body oils, organic oil additives, mineral oil, skin cells, nail clippings etc that can accumulate both in the basin and the jets which may become a fertile area for micro organisms to grow.

The use of oil based products can build up in the whirlpool system causing clogging in the jets. Adherence to the above cleaning will minimize build up. Gulfstream Plastics Ltd does not recommend the use of mineral oil based products.

TESTING/FLUSHING FOOT SPA

After foot spa has been installed, fill tub with water just above the jets. Carefully check for leaks at drain and over flow. After checking underside for leaks turn on system by pushing whirlpool button and watch for leaks as water circulates. Let tub run full cycle. Open drain plug for water discharge.

WARRANTY & SERVICE

Gulfstream warrants to the original purchaser that the new pedicure spa will be free from defect during the Standard Warranty Period (listed below). The shipping date and the uniquely-coded Serial Number on the back of each spa chair will justify the start of the warranty period for the product. The warranty is null and void if the pedicure spa is taken from its initial place of installation, or it is not installed in accordance with federal, state or local codes and ordinances. Also, this warranty does no apply if the pedicure spa has been subject to misapplication, improper installation or maintenance, negligence, improper cleaning or other circumstances beyond Gulfstream's control.

Warranty

1. Limited Three(3) Years warranty on Spa Shell.
2. Limited One(1) Year warranty on the Whirlpool Pump.
3. Limited One(1) Year warranty on the Clean Jet.
4. Limited One(1) Year warranty on the Glass Bowl.
5. Limited One(1) Year Parts-Only warranty which covers the Hydraulic System, Discharge Pump, Massage System and All Electrical Components.
6. Gulfstream will pay shipping charges on all replacement parts during the first 90 days of the stated Warranty Period. After 90 days the consumer is responsible for all labor and shipping costs incurred.

Exclusions

1. Damage to pump parts and/or motor parts due to obstruction in plumbing lines etc.
2. Staining, fading or discoloration of plastic surfaces due to exposure and/or the use of harmful cleaning agents or Chemicals.
3. Staining, fading or discoloration caused by improper or poor water additives not related to the maintenance of Proper water are not covered by this warranty.
4. Staining, fading or discoloration of the seat, armrests or footrests.
5. Freight damage, misuse, neglect, accident, natural disaster and abuse.
6. Unauthorized repairs.

Service

1. The Dealer shall forward all warranty-related matters to our Customer Service Department.
2. Serial Numbers and Original Invoice must accompany all warranty claims.
3. Customers are responsible for shipping defective parts back to Gulfstream. These parts must be packaged correctly in order to protect against any further damage.
4. All parts are to be shipped by UPS Ground Service average 2-5 days.
5. All defective parts must be shipped back to Gulfstream within 30 days of receiving the new replacement parts or warranty will be void.
6. Any warranty claim that cannot be determined over the phone, the customer must send photos and original invoice directly to Gulfstream before any repairs can be performed.
7. Any service performed on the product without Gulfstreams authorization will also void the Warranty.
8. Each service call from the customer will be assigned a Claim Number. The Claim Number will stay open until the problem is resolved.

No dealer or other person has any authority to bind Gulfstream Plastics Ltd. to changes or additions to this warranty or its products. Accordingly, Gulfstream Plastics Ltd. is not responsible for such warranties or representations.

Manufacturer of Acrylic Bath
Whirlpool & Pedicure Foot Spas

Gulfstream Plastics Ltd.
Cambridge, Ontario, Canada N1R 6T4

Tel.: 519-622-0950
Fax: 519-622-6926
www.gulfstreamplastics.com

© 2009 All rights reserved. Design and Specifications are subject to change without notice